



5.1 AV Receiver

AV-9600

dts/Dolby Digital 5.1 AV Receiver



Features

Video Input x 3 (DVD, Video 1, Video 2), Output x 1
 S-video Input x 3 (DVD, Video 1, Video 2), Output x 1
 Component (Y, Cb, Cr) Input x 2 (DVD, Video 1), Output x 1

Optical Input x 2, Output x 1
 Coaxial Input x 1
 Direct 5.1 Channel Input, Direct 5.1 Pre-Amp Output
 Line In x 6 (DVD, Video 1, Video 2, Video 3, Tape, Aux)
 Front AV (Video 3) Input
 Digital AM/FM Tuner (20 Preset stations)

Specifications

Audio Section

Rated power Output:
 FRONT 100W+100W(8Ω, RMS, THD ≤ 0.1%)
 CENTRE 100W(8Ω, RMS, THD ≤ 0.1%)
 REAR 100W+100W(8Ω, RMS, THD ≤ 0.1%)

Output Impedance:
 FRONT 8 ohm
 CENTRE 8 ohm
 REAR 8 ohm

Total Harmonic Distortion: Less than 0.05%

Line Input

Input sensitivity/Impedance: 150 mV/47k.
 Frequency Response: 20Hz-25Hz +0.5/-1 dB
 Tone Control Range: BASS: +6 dB
 TREBLE: +6 dB
 Signal-noise Ratio: 75 dB

Woofers Output

Rated Output/Impedance: 150mV/10K.
 Frequency Response: 10Hz-300Hz ±3 dB

FM Tuner Section

Frequency Range: 87.5-108MHz
 Sensitivity: 14dB(µV)
 Antenna Terminal: 75 ohm(unbalanced)

AM Tuner Section

Frequency Range: 522-1629kHz
 Sensitivity: 68 dB/M
 Single-to-noise Range: 30 dB
 Antenna: Loop Antenna

General

Power Requirements: AC 220-240V~50-60Hz
Max. Power Consumption: 500Watts
Dimensions: 430(W) x 150(H) x 350(D)mm
Net Weight: 15.8Kg

Sole Agent

*Design and specifications are subject to change without notice.



Wo Kee Hong Limited

10/F., Block A, 585-609 Castle Peak Road, Kwai Chung, New Territories, H.K.
 Tel: 2868 2350 Fax: 2869 1581