

Rogers®

BRITISH HIGH-FIDELITY

RT-9000

6.1 Digital Surround Home Theatre

RT-939TS

*Aluminium Front / Surround /
Centre Tower Speakers*

RT-939

AV Receiver

Specification

Audio Section

Rated power Output:

FRONT : 50W+50W (4Ω)

CENTER : 50W + 50W (4Ω)

REAR : 50W+50W (4Ω)

Total Harmonic Distortion: Less than 0.1%

Line Input

Input sensitivity/Impedance: 150 mV /47kΩ

Frequency Response: 20Hz-20kHz +0.5/-1 dB

Tone Control Range: BASS: +6 dB

TREBLE: +6 dB

Signal-noise Ratio: 75 dB

*Design and specifications are subject to change without notice.

Sole Agent



Wo Kee Hong Limited

10/F., Block A, Wo Kee Hong Bldg.

585-609 Castle Peak Road, Kwai Chung, N.T. Hong Kong

Tel : (852) 2868 2350 Fax : (852) 2869 1581



ASB-108

Active Subwoofer

FM Tuner Section

Frequency Range: 87.5-108MHz

Sensitivity: 14dB(5uV)

Antenna Terminal: 75 ohm(unbalanced)

MW Tuner Section

Frequency Range: 522-1629kHz, 9kHz step

Sensitivity: 68 dB/M

Single-to-noise Range: 30 dB

Antenna: Loop Antenna

Video Section

Standard Video Jacks

Input and Output 1 V p-p/75Ω

Level/Impedance:

General

Power Requirements: AC230V ~50Hz

Power Consumption: 180Watts

Dimensions: 430(W)x296(D)x67(H)mm

Weight: 7.5Kg